



# HYPERION TUBE DATASHEET



## Optical

### Colours

Customized RGB-Mint-Amber

### Total LED power

144W

### Max. power draw

92W

### Emittance (at 1m)

1570Lx

### TLCI

≥96

### CRI

≥96

### Beam Angle

180°

### Pixels

32

## Electrical

### Battery

LG Chem Lithium-ion

### Battery Lifetime

70% after 300 cycles

### Battery Runtime

Up to 20 hours

### LED Lifetime

50.000 Hours

### Charging time (nominal)

3 Hours

### Input Voltage (Charger)

90-264V 47-63Hz

### Input Voltage (Light)

24V, 4A

## Control

### Backside display

With HSI control

### Wireless Modules

865-870MHz | 902-928MHz |

2.4GHz

### Range

300m | 330 Yards

### DMX

Wired DMX + Wireless (CRMX & W-DMX)

## Construction

### Housing

Polycarbonate, metal end caps

### IP Rating

IP65

### Relative humidity

0-100%

### Operating Temperature

0-40 °C

32-104 °F

### Weight

2.90kg

6.39Lbs

### Dimensions

Ø42 x 2031 mm

Ø1.6" x H66.43"

## Accessories



### Charger

FP3-CHR



### Eyebolt

AX1-EBLT (2 pieces Included)



### Holder

AX1-H (2 pieces included)



### BabyPin (3/8" & 1/4"-20 threads)

AX1-BLT



### WingPlate

AX1-WP (Does not include holders)



### CrossPlate

AX1-CP



### Connection cable

FP1-PWB-CAB



### Extension Cable

FP1-EXC



### DataLink

FP1-DTL